

Version 17.1 replaces Version 16.1 Revision date: 01.01.2017 According to (EU) No. 2015/830

SECTION 1

IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier: BYCOTEST® D30A - aerosol

1.2 Relevant identified uses of the mixture and uses advised against:

Relevant identified uses: Solvent developer used in penetrant

inspection.

Uses advised against: This product is not recommended for any

use other than the identified uses above.

1.3 Details of the supplier of the safety data sheet

Manufacturer: Magnaflux® (A Division of ITW Ltd)

Address: Faraday Road, South Dorcan Industrial

Estate, Swindon, UK

Postcode: SN3 5HE

Telephone/fax number: Telephone: +44 (0)1793 524566

Fax: +44 (0)1793 490459

Web: www.eu.magnaflux.com datasheets@magnaflux.co.uk

Email address of competent person

responsible for SDS:

National contact: None appointed.

1.4 Emergency telephone number: DURING OFFICE HOURS, CALL

T: +44 (0)1793 524566 (English only)

Opening hours: Office hours (GMT) Monday - Thursday 8am

- 5pm, Friday 8am - 4pm

OUT OF OFFICE HOURS, CALL

T: +44(0)203 394 9866

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

Classification according to Regulation Physical and Chemical Hazard:

(EC) No 1272/2008 (CLP): Aerosol 1 H222, H229 Health Hazard:

None

Environmental Hazard:

None

Additional information No additional information.

For full text of hazard statements and EU hazard statements see SECTION 16.

2.2 **Label Elements:**

Labelling according to regulation (EC) No 1272/2008 [CLP]

Hazard Pictograms:

Signal Word: Danger

Hazard Statement(s): H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if

heated.

Precautionary Statement(s): P210: Keep away from heat/sparks/open

> flames/hot surfaces - No smoking P211: Do not spray on an open flame or

other ignition source.

P251: Do not pierce or burn even after use. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P280: Wear protective gloves/protective clothing/eye protection/face protection P501: Dispose of contents/container to hazardous waste or special collection point.

Supplementary Precautionary

Statement(s):

P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with

water/shower No Supplemental Information

Supplementary Hazard Information

(EU)

Hazard Determining Component(s)

Not applicable.

2.3 Other hazards:

None

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 **Mixtures**

Ingredient Name	CAS No	EC No	REACH Registration Number	% Weight	Classification according to Regulation (EC) No 1272/2008 [CLP]	Additional information
Ethanol	64-17-5	200-578-6	01- 2119457610-43	< 60	Flam. Liq. 2 H225	
Ethyl acetate	141-78-6	205-500-4	01- 2119475103-46	< 5	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE3 H336	EUH066
Calcium Carbonate	471-34-1	207-439-9		< 10	None	Has WEL
Hydrocarbons, C3-4- rich petroleum distillate petroleum gas (1.3 butadiene < 0.1%)	68512- 91-4	270-990-9	(note1)	15-40	Press. Gas H280 Flam. Gas 1 H220	(note2)
 Exempted from 	the obligation	n to register ir	n accordance with a	art.2(7)(a) o	f REACH Regulation No 1907/20	006

Not classified as carcinogen, less than 0.1% w/w 1,3 butadiene (EINECS no 203-450-8)

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished

*See Section 16 for hazard statement(s) text in full.

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures:

General notes: If symptoms persist, seek medical attention.

Show this safety data sheet to the doctor in

attendance.

Following inhalation: Remove to fresh air. Keep at rest. If not

breathing give artificial respiration. Seek medical attention if symptoms occur.

Following skin contact: Flush with water, use soap if available.

Contaminated clothing should be washed before re-use. Seek medical attention if

irritation persists.

Following eye contact: Flush eyes with large amounts of water for

at least 10 minutes. Seek medical attention

if irritation persists.

Following ingestion: Unlikely route of exposure. Do NOT induce

vomiting. Never give anything by mouth to an unconscious person. Seek medical

attention immediately.

Self-protection of the first aider: No action shall be taken involving any

personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate personal protective

equipment.

4.2 Most important symptoms, both acute and delayed:

No delayed effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

None known.

SECTION 5 FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media: Carbon dioxide, foam, dry chemical, water

fog or spray.

Unsuitable extinguishing media: High pressure water jet.

5.2 Special hazards arising from the Evacuate immediate area. Shut off 'fuel' to

substance or mixture: fire. If possible keep unaffected containers

cool with water spray.

Aerosols may explode in a fire.

Aerosol contents are extremely flammable.

Hazardous combustion products: Smoke, soot and oxides of carbon. Burning

vapour may give off toxic fumes.

5.3 Advice for fire-fighter:

Warn firefighters that aerosols are involved.

Self contained breathing apparatus and full protective clothing must be worn. Cool containers exposed to flames with water until well after the fire is out.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Suitable protective equipment (see Section 8) should be worn to prevent any

contamination of skin, eyes and personal clothing.

For non-emergency personnel: Remove ignition sources. Avoid breathing

vapours, spray or mist. Ensure adequate

ventilation.

For emergency responders: Keep unnecessary people at a safe

distance. Remove ignition sources. Avoid breathing vapours, spray or mist. Ensure

adequate ventilation.

6.2 Environmental precautions:

Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs.

6.3 Methods and material for containment and cleaning up:

Eliminate sources of ignition. Take measures to prevent the build-up of electrostatic

charge. Ventilate well.

For containment: Contain spillage, and then collect with non-

combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a UN approved container for

disposal.

Large spills should be pumped (using an earthed explosion proof pump) into UN approved containers pending disposal. Dispose of waste according to local/national

regulations.

For cleaning up: Pick up with suitable absorbent material.

Rinse site with copious amounts of water, which should not be allowed into drains,

sewers or watercourses.

Other information: No other information.

6.4 Reference to other sections:

For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SECTION 7 HANDLING & STORAGE

7.1 Precautions for safer handling:

Protective Measures: Wear suitable protective clothing such as

chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when

in use.

Avoid contact with skin and eyes. Do not

breathe product spray or mist.

Measures to prevent fire: Aerosol contents are highly flammable and

volatile. Keep away from sources of ignition

no smoking.

Take measures to prevent the build-up of

electrostatic charge.

Equipment should be earthed. Use

explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

Advice on general occupational

hygiene:

Wash thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities:

Technical measures and storageStore in a cool dry area away from heat and

conditions: sources of ignition.

Packaging materials: Store in original container.

Requirements for storage rooms and

vessels:

Pressurised container: protect from sunlight

and do not expose to temperatures

exceeding 50 °C.

Recommended storage temperature 10 °C

to 30 °C.

Further information on storage

conditions:

Rotate stock and check regularly for

damaged items.

7.3 Specific end use(s):

Recommendations:

Use only for Non Destructive Testing (NDT)

applications.

Industrial sector specific solutions: See product data sheet for further

information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

		Limit value - 8 hours		Limit value -	short term
Ingredient name	Country	ppm	mg /m3	ppm	mg/m3
Ethanol	UK	1000	1920		
	Germany (AGS)	500	960	1000 (1)	1920 (1)
	Sweden	500	1000	1000 (1)	1900 (1)
Ethyl acetate	UK	200	730	400	1460
	Germany (AGS)	400	1500	800 (1)	3000 (1)
	Sweden	150	500	300 (1)	1100 (1)
Calcium carbonate (inhalable aerosol)	UK		10		
Calcium carbonate (respirable aerosol)	UK		4		

^{(1) 15} minutes average value

Data obtained from GESTIS International Limit Values, EH40, supplier's SDS

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) - Ethanol

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	950 mg/m ³
Worker	Inhalation	Short term	Local	1900 mg/m ³
Worker	Dermal	Long term	Systemic	343 mg/kg bw/day

Derived No Effect Level (DNEL) - Ethyl acetate

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	734 mg/m ³
Worker	Inhalation	Short term	Systemic	1468 mg/m ³
Worker	Dermal	Long term	Systemic	63 mg/kg bw/day

Derived No Effect Level (DNEL) - Calcium carbonate

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	10 mg/m3

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygenists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC)

,	Éthanol	Ethylacetate	Calcium carbonate	
Water - Fresh Water	0.96 mg/l	0.24 mg/l	-	
Water - Marine Water	0.79 mg/l	0.024 mg/l		
Water - Intermittent release	2.75 mg/l	1.65 mg/l	No data available.	
Sediment - Fresh water	3.6 mg/kg dw	650 mg/kg dw	INO data avallable.	
Sediment - Marine water	2.9 mg/kg dw	1.15 mg/kg dw		
Soil	0.63 mg/kg dw	0.115 mg/kg dw		
Sewage Treatment plant	580 mg/l	0.148 mg/l	100 mg/l	

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded. If ventilation is insufficient suitable respiratory protection must be provided.

Personal protection equipment: Eye and face protection:

Skin protection - hand:

Safety glasses with side-shields conforming to EN166.

Protective gloves conforming to EN374-3. Use chemical resistant gloves recommended by glove manufacturer as being suitable for **alcohols**, if hand exposure is unavoidable.
Butyl and Neoprene are suitable, although other types may be more suitable in other circumstances.
For prolonged exposure, recommended gloves with a protective index 6, > 480 minutes permeation time according to

EN374.

As the product is a preparation, consult the glove manufacturer for exact breakthrough time. Glove manufacturer's directions for use should be observed. Wear chemical resistant overalls if skin contact is likely. Wear impervious, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at

the specific workplace.

Skin protection - other:

Respiratory protection:Use a respirator with appropriate canister

type filter cartridge if spraying in confined or unventilated areas. Use respiratory equipment with gas filter type A2P3

(EN141).

Use respirators and components tested and approved under CEN standards.

Thermal hazards: Not applicable

Environmental exposure controls: Avoid any release to the environment.

SECTION 9 PHYSICAL & CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance: Aerosol containing mobile white liquid.

Odour: Solvent – alcoholic.
Odour threshold: No data available.
pH: No data available.

Melting point/freezing point: <-80 °C. Initial boiling point and boiling range: 78 °C.

Flash point (PMCC): -40 °C (aerosol propellant)

Evaporation rate (BuAC = 100):

Flammability (solid, gas) (Limits in air):

Upper/lower flammability or explosive

No data available.

No data available.

3.5 – 19% (Vol %)

limits:

Vapour pressure: No data available.

Vapour density (Air = 1):> 1.Relative density:0.94 g/cm³.Solubility:Soluble.

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Decomposition temperature:

Viscosity (ASTM D445):

Explosive properties:

No data available.

Note: properties relate to the bulk product only unless otherwise stated.

9.2 Other information:

No other information

SECTION 10 STABILITY & REACTIVITY

10.1 Reactivity: No data available.

10.2 Chemical stability Stable under normal conditions of use and

applications.

10.3 Possibility of hazardous reactions: No data available.

10.4 Conditions to avoid: Keep away from sources of ignition, hot

surfaces, direct sunlight and static

discharge.

10.5 Incompatible materials: Strong oxidising agents. Acids and alkalis.

10.6 Hazardous decomposition materials: None under normal conditions of storage

and use. Smoke, soot and oxides of carbon

on combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: based on data for component materials.

Acute toxicity - oral: Based on the available data the classification

criteria are not met.

Acute toxicity – dermal: Based on the available data the classification

criteria are not met.

Acute toxicity – inhalation: Based on the available data the classification

criteria are not met.

Skin corrosion/irritation:Based on the available data the classification

criteria are not met.

Serious eye damage/irritation: Based on the available data the classification

criteria are not met.

Respiratory sensitisation: Based on the available data the classification

criteria are not met.

Skin sensitisation: Based on the available data the classification

criteria are not met.

Germ cell mutagenicity:Based on individual components, this

preparation is not expected to show

mutagenic effects.

Carcinogencity: Based on individual components, this

preparation is not expected to show

carcinogenic effects.

Reproductive toxicity:Based on individual components, this

preparation is not expected to show

reproductive toxicity.

STOT single exposure: Based on the available data the classification

criteria are not met.

STOT repeated exposure: Based on the available data the classification

criteria are not met.

Aspiration hazard: Based on the available data the classification

criteria are not met.

Information on likely Routes of Exposure and Potential Health Effects:

Inhalation: Vapour concentrations above the

recommended exposure levels are irritating to

the eyes and respiratory tract.

Ingestion: Not a likely route of entry. However, ingestion

may cause irritation of the mouth, throat and digestive track. Absorption of large amounts

may cause systemic effects.

Eye contact: Can cause eye irritation.

Skin contact: May be harmful of absorbed through skin.

May cause skin irritation.

Repeated exposure may cause skin dryness

or cracking.

Toxicity Test Results: based on data for component materials, where available.

Ethanol

Acute Toxicity – oral	LD50 (rat)	> 2000 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	> 2000 mg/kg
Acute Toxicity – inhalation	LC50 (mouse)	> 20 mg/l vapours 4 hours

Ethyl acetate

Acute Toxicity – oral	LD50 (rat)	5620 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	> 20000 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	30 mg/l

Calcium carbonate

Acute Toxicity – oral	LD50 (rat)	> 2000 mg/kg
Acute Toxicity – dermal	LD50 (rat)	> 2000 mg/kg

Other Information: No other information.

SECTION 12 ECOLOGICAL INFORMATION

Based on data for component materials

12.1 Toxicity:

Ethanol

Fish	Leuciscus idus	LC50	48 hours	> 100 mg/l
Aquatic Invertebrates	Daphnia magna	EC50	48 hours	> 100 mg/l
Aquatic Plants	Selenastrum capricornutum	EC50	48 hours	> 100 mg/l

Ethyl acetate

Fish	Pimephales promelas	LC50	96 hours	230 mg/l
Aquatic Invertebrates	Daphnia magna	EC50	48 hours	717 mg/l
Aquatic Plants	Desmodesmus subspicatus	EC50	48 hours	3300 mg/l
Microorganisms	Pseudomonas putida	EC10	16 hours	2900 mg/l

Calcium carbonate

Fish	Gambusia affinis	LC50	96 hours	> 5600 mg/l
Aquatic Invertebrates	Daphnia magna	LC50	48 hours	> 100 mg/l
Aquatic Plants	Desmodesmus subspicatus	EC50	72 hours	> 14 mg/l
Microorganisms	Activated sludge	EC50	3 hours	1000 mg/l

12.2 Persistence and degradability: Expected to be biodegradable.

12.3 Bioaccumulative potential: This preparation does not contain any

substances expected to be bioaccumulative.

Partition coefficient: n-octanol/water

Bioconcentration factor (BCF):

(log Kow):

No data available.

-0.31 (ethanol)

12.4 Mobility in soil: This product is miscible with water.

12.5 Results of PBT and vPvB assessment: This mixture does not contain any

substances that are assessed to be a PBT or

vPvB.

12.6 Other adverse effects: No data available.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.

Product/packing disposal: Empty containers may contain residual

product and flammable vapours. Do not pierce or burn container, even after use. Keep away from sources of ignition. Do

NOT remove labels.

Waste codes/waste designations

according to LoW:

16 05 04* gases in pressure containers containing dangerous substances

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

Waste treatment – relevant information: Dispose of waste and residues in

accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation

Sewage disposal – relevant

information:

Other disposal recommendations:

Use a licensed waste contractor.

Do not empty down the drain.

SECTION 14 TRANSPORT INFORMATION

14.1	UN number:	ADR/RID:	UN1950
		IMDG:	LIN1950

IMDG: UN1950 IATA: UN1950

14.2 UN proper shipping name: ADR/RID: AEROSOLS, flammable

IMDG: AEROSOLS, flammable IATA: AEROSOLS, flammable

14.3 Transport hazard class(es): ADR/RID: 2.1

IMDG: 2.1 IATA: 2.1

14.4 Packing group: ADR/RID: N/A

IMDG: N/A IATA: N/A

14.5 Environmental hazards: ADR/RID: No

IMDG: Marine Pollutant: No

IATA: No

14.6 Special precautions for user:

 ADR/RID – Tunnel code:
 (D)

 IMDG – Ems:
 F-D, S-U

 IATA/ICAO – PAX:
 203

 IATA/ICAO – CAO:
 203

14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC code:

Not applicable.

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations:

This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures. Safety data sheet as required by EC Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.

Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.

This data sheet is complied according Dir 2013/10/EU, 2008/47/EEC amendment of the aerosol directive 75/324/EEC.

Extra label elements: Pressured container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

National regulations (Germany):

Wassergefahrdungklasse (water WGK 1 – Low hazard to waters.

hazard class):

Technische Anleitung Luft (TA-Luft): Class 5.2.5 Organic substances, except

dusts.

15.2 Chemical safety assessment:

No chemical safety assessment has been carried out for this mixture by the supplier.

SECTION 16 OTHER INFORMATION

(i) Indication of changes:

Version 17.1 updated in Section 1.4.

Vertical lines on the left hand side indicate an amendment from the previous version.

(ii) Abbreviations and acronyms:

ADR European Agreement concerning the International Carriage of Dangerous Goods

by Road (Accord européen relatif au transport international des marchandises

Dangereuses par Route)

CAS No. Chemical Abstracts Service number
CEN European Committee for Standardisation

CLP Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008

ECHA European Chemicals Agency

EC50 Half Maximal Effective Concentration

EC number EINECS and ELINCS number

EINECS European Inventory of Existing Commercial Substances

ELINCS European List of notified Chemical Substances

GHS Globally Harmonized System

IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC50 Lethal Concentration to 50% of a test population

LD50 Lethal Dose to 50% of a test population

MPI Magnetic Particle Inspection
NDT Non-Destructive Testing
OEL Occupational Exposure Limit

PBT Persistent, Bioaccumulative and Toxic Substance

PMCC Pensky-Martens closed cup method PPE Personal Protection Equipment

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

EC (No) 1907/2006

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

(Reglement International concernant le transport des marchandises Dangereuses

par chemin de fer)

SDS Safety Data Sheet

STOT RE Specific Target Organ Toxicity, Repeat Exposure STOT SE Specific Target Organ Toxicity, Single Exposure

TA-Luft Technical Instructions on Air Quality Control (Technische Anleitung zur

Reinhaltung der Luft)

vPvB Very Persistent and Very Bioaccumulative

WEL Workplace Exposure Limit

WGK German Water Hazard Class (Wassergefährdungsklasse)

(iii) Key literature and sources of data:

- Supplier's safety data sheets for components listed in Section 3.
- European Chemicals Agency, http://echa.europa.eu/
- GESTIS International Limit Values Database, http://limitvalue.ifa.dguv.de/Webform_gw.aspx
- Occupational Exposure Limits EH40/2005.
- Commission regulation (EU) 2015/830.
- Control of Substances Hazardous to Health Regulations 2002.
- Hazardous waste regulations 2005.
- Health & Safety at Work Act 1974.
- Regulation (EC) No. 1907/2006 (REACH).
- Regulation (EC) No. 1272/2008 (CLP)

(iv) Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):

Classification according to Regulation (EC) No 1272/2008	Classification procedure
Aerosol 1 H222, H229	Test

(v) Hazard statements (number and full text):

H220: Extremely flammable gas

H222: Extremely flammable aerosol

H229: Pressurised container: May burst if heated.

H225: Highly flammable liquid and vapour

H280: Contains gas under pressure; may explode if heated

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

Hazard Class Category Code (number and full text):

Aerosol 1: Aerosol

Flam. Liq. 2: Flammable liquid Flam. Gas: Flammable gas

Press. Gas: Gases under pressure

Eye Irrit. 2: Serious eye damage/eye irritation

STOT SE3: Specific target organ toxicity - single exposure

Relevant precautionary statements (number and full text):

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn even after use.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P280: Wear protective gloves/protective clothing/eye protection/face protection

P501: Dispose of contents/container to hazardous waste or special collection point.

P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

(vi) Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment. Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-to-date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

Revision summary: Revision Comments This SDS is valid from the Revision Date. If you

require a SDS for the product manufactured before

the Revision Date please contact us at

datasheets@magnaflux.co.uk.

Revision Date 01.01.2017

Version 17.1